# Inspecam® LX

## **Cameras with power LED**



## **Inspecam LX Standard**

Robust and affordable cameras with powerful 10 W LED (equiv to 80 W halogen)

Inspecam LX Standard: For surveys of

oceanographic applications and general use in harsh environments.

**Inspecam LX Borehole**: Camera (3.5 kg) for vertical inspections. Visual examination of boreholes from 60 mm diameter, tanks, mines, etc.



**Inspecam LX Borehole** 

SPECIFICATIONS TYPE OPTICAL	HD	SD
Lens View angle air (diag) View angle water (diag) Focus	2.8 130° 90° Fixed	2.8 mm 130° 90° Fixed

Image sensor	1/2.9" Sony	1/2.9" Sony
Resolution	2 MP	700TVL
Minimum illum	0.05 lux	0.05 lux
Format	16:9	4:3
S/N ratio	>52 dB	>52 dB
White balance	Auto	Auto
Output signal	AHD	CVBS
Supply	12V DC	12V DC
Light source	Power LED	Power LED
Power	10 Watt	10 Watt
Luminous output	2950 lm	2950 lm

## **MECHANICAL**

**ELECTRICAL** 

Housing	Stainless steel	Stainless steel / Aluminium 6061
Window	BK7 glass	BK7 glass
Diameter	50 mm	50 mm
Length	320 or 120	120 mm (excluded connector)
Weight in air	3.5 kg	1.4 / 0.5 kg
Weight in water	3 kg	1.2 / 0.42 kg

### **ENVIRONMENT**

Rated depth 1000 m (waterproof 10 MPa /100 bar) Operating temperature  $-10^{\circ}\text{C}$  to  $50^{\circ}\text{C}$ 

#### **APPLICATIONS**

Inspecam LX Borehole: Boreholes, wells, tanks, pipes and places of limited space. Inspecam LX Standard: General applications in underwater inspection.

